

Material Safety Data Sheet

From: Vinquiry, Inc. 7795 Bell Road Windsor, CA 95492



24 hour Emergency Telephone: Chemtrec: 1-800-424-9300

Outside U.S. and Canada Chemtrec: 202-483-7616

NOTE: CHEMTREC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

All Non-emergency questions should be directed to Customer Service (1-707-838-6312) for assistance.

1% Copper Sulfate

10% Copper Sulfate

COPPER SULFATE 0.2%-10%

MSDS Number: CS054--- Effective date 01/01/04

1. Product Identification

Synonyms: Copper (II) Sulfate Pentahydrate (1:1:5); blue vitriol; Sulfuric acid copper (2+) salt (1:1),

Pentahydrate

CAS No.: 7758-98-7 (Anhydrous) 7758-99-8 (Pentahydrate)

Molecular Weight: 249.68

Chemical Formula: CuSO₄ 5H₂O in H₂O

Vinguiry Product Codes: 10-054-0000, 10-054-0118, 10-054-0237, 10-054-0473, 10-054-0946, 10-

055-0000, 10-055-0118, 10-055-0237, 10-055-0473, 10-055-0946

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous	
Cupric Sulfate	7758-98-7	0.2-10%	Yes	
Water	7732-18-5	90-99.8%	No	

3. Hazards Identification

Emergency Overview

WARNING! HARMFUL IF SWALLOWED. AFFECTS THE LIVER AND KIDNEYS. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT.

Vinquiry Safety Data Ratings (Provided here for your convenience)

Health Rating: 2 - Moderate Flammability Rating: 0 - None Reactivity Rating: 0 - None Contact Rating: 2 - Moderate

Lab Protective Equip: GOGGLES; LAB COAT; VENT HOOD; PROPER GLOVES

Storage Color Code: Orange (General Storage)

Potential Health Effects

Inhalation:

Causes irritation to respiratory tract, symptoms may include coughing, sore throat, and shortness of breath. May result in ulceration and perforation of respiratory tract. When heated, this compound may give off copper fume, which can cause symptoms similar to the common cold, including chills and stuffiness of the head.

Ingestion:

May cause burning pain in the mouth, esophagus, and stomach. Hemorrhagic gastritis, nausea, vomiting, abdominal pain, metallic taste, and diarrhea may occur. If vomiting does not occur immediately systemic copper poisoning may occur. Symptoms may include capillary damage, headache, cold sweat, weak pulse, kidney and liver damage, central nervous excitation followed by depression, jaundice, convulsions, blood effects, paralysis and coma. Death may occur from shock or renal failure. Fatalities have occurred as a result of ingesting gram quantities of copper sulfate.

Skin Contact:

May cause irritation and itching.

Eve Contact:

Dust may cause irritation. Contact may cause conjunctivitis, ulceration, or clouding of the cornea.

Chronic Exposure:

Prolonged or repeated skin exposure may cause dermatitis. Prolonged or repeated exposure to dusts of copper salts may cause discoloration of the skin or hair, blood and liver damage, ulceration and perforation of the nasal septum, runny nose, metallic taste, and atrophic changes and irritation of the mucous membranes.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders, impaired liver, kidney, or pulmonary function, glucose 6-phosphate-dehydrogenase deficiency, or pre-existing Wilson's disease may be more susceptible to the effects of this material.

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Ingestion:

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Call a physician immediately.

Skin Contact:

In case of contact, wipe off excess material from skin then immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Not considered to be a fire hazard.

Explosion:

Not considered to be an explosion hazard. Sealed container may rupture during fire conditions from pressure water vapor release.

Fire Extinguishing Media:

Use any means suitable for extinguishing surrounding fire. Water spray may be used to keep fire exposed containers cool.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. When heated above 110C (230F) material will melt. Avoid using a direct water stream on molten material as it may causes splattering.

6. Accidental Release Measures

Ventilate area of leak or spill. Keep unnecessary and unprotected people away from area of spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Pick up and place in a suitable container for reclamation or disposal, using a method that does not generate dust. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from incompatible substances. Solutions are corrosive to mild steel. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

-OSHA Permissible Exposure Limit (PEL):

1 mg/m3 (TWA) for copper dusts & mists as Cu

-ACGIH Threshold Limit Value (TLV):

1 mg/m3 (TWA) for copper dusts & mists as Cu

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest.. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear protective gloves and clean body-covering clothing.

Eve Protection:

Use chemical safety goggles. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance:

Blue liquid.

Odor:

Odorless.

Solubility:

31.6g/100cc H20 @ 0C (32F)

Specific Gravity:

2.28 @ 15.6C/4C

pH:

4.0 (0.2 M solution)

% Volatiles by volume @ 21C (70F):

0

Boiling Point:

> 150C (> 302F) Decomposes with loss of 5H2O

Melting Point:

110C (230F) Loses 4H2O @ this temperature.

Vapor Density (Air=1):

No information found.

Vapor Pressure (mm Hg):

No information found.

Evaporation Rate (BuAc=1):

(water=1): slowly efflorescent.

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

When heated to decomposition cupric oxide and sulfur oxide may form.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Substance will ignite hydroxylamine. Solutions are acidic and can react with magnesium to evolve flammable hydrogen gas. May react with acetylene to form dangerous acetylides.

Conditions to Avoid:

Incompatibles.

11. Toxicological Information

Oral rat LD50: 300 mg/kg. Investigated as a tumorigen, mutagen.

\Cancer Lists\				
	NTP Carcinogen			
Ingredient	Known	Anticipated	IARC Category	
Cupric Sulfate (7758-98-7)	No	No	None	

12. Ecological Information

Environmental Fate:

Data for anhydrous material unless otherwise noted. When released into the soil, this material is not expected to biodegrade. When released into the soil, this material may leach into groundwater. When released into water, this material is not expected to biodegrade. When released into water, this material is not expected to evaporate significantly. This material is expected to significantly bioaccumulate. This material has an experimentally-determined bioconcentration factor (BCF) of greater than 100. Bioaccumulation data for copper.

Environmental Toxicity:

This material is expected to be very toxic to aquatic life. The LC50/96-hour values for fish are less than 1 mg/l. The IC50/72-hour values for algae are less than 1 mg/l. Toxicity data for copper.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(CUPRIC SULFATE)
Hazard Class: 9
IIN/NA: IIN3077

UN/NA: UN3077 Packing Group: III

Information reported for product/size: 400LB

International (Water, I.M.O.)

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(CUPRIC SULFATE) **Hazard Class:** 9

UN/NA: UN3077 Packing Group: III

Information reported for product/size: 400LB

International (Air, I.C.A.O.)

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(CUPRIC SULFATE) **Hazard Class:** 9 **UN/NA:** UN3077
Packing Group: III

Information reported for product/size: 400LB

15. Regulatory Information

\Chemical Inventory Status - Part 1\					
Ingredient	TSCA	EC	Japan	Australia	
Cupric Sulfate (7758-98-7)	Yes	Yes	Yes	Yes	
\Chemical Inventory Status - Part 2\					
	Canada				
Ingredient	Korea	DSL	NDSL	Phil.	
Cupric Sulfate (7758-98-7)	Yes	Yes	No	Yes	

```
-----\Federal, State & International Regulations - Part 1\-----
                         -SARA 302- -----SARA 313-----
                               RQ TPQ List Chemical Catg.
 Ingredient
 No No No Copper compo
 Cupric Sulfate (7758-98-7)
 -----\Federal, State & International Regulations - Part 2\-----
                                       -RCRA- -TSCA-
                                      -RCRA-
261.33
                               CERCLA
                                              8(d)
 Ingredient
                                              _____
 10
                                      No
 Cupric Sulfate (7758-98-7)
                                              No
Chemical Weapons Convention: No TSCA 12(b): No CDTA: No
SARA 311/312: Acute: Yes Chronic: Yes Fire: No Pressure: No
Reactivity: No (Pure / Solid)
```

Australian Hazchem Code: None allocated.

Poison Schedule: S5

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: **2** Flammability: **0** Reactivity: **0**

Label Hazard Warning:

WARNING! HARMFUL IF SWALLOWED. AFFECTS THE LIVER AND KIDNEYS. CAUSES IRRITATION TO SKIN. EYES AND RESPIRATORY TRACT.

Label Precautions:

Avoid contact with eyes, skin and clothing.

Wash thoroughly after handling.

Avoid breathing dust.

Keep container closed.

Use only with adequate ventilation.

Label First Aid:

If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. In case of contact, wipe off excess material from skin then immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In all cases, get medical attention.

Product Use:

Laboratory Reagent.

Revision Information:

None.

Disclaimer

Vinquiry Inc. provides this information in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to laboratory use of this material by a properly trained person. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Vinquiry Inc. will not be responsible for damages resulting from use or reliance upon this information.