

MATERIAL SAFETY DATA SHEET

PASTE WOOD FILLER

Page: 1

PRODUCT NAME: PASTE WOOD FILLER
PROCUCT CODE: 2701-2704

HMIS CODES: H F R P
1* 2 0 B

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME : JASCO Chemical Corp.
ADDRESS : 1008 N. Fuller St.
Santa Ana, CA. 92701

EMERGENCY PHONE : 800-424-9300 DATE PRINTED : 6/01
INFORMATION PHONE : (714) 547-6951 NAME OF PREPARER : RE

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 4 columns: REPORTABLE COMPONENTS, CAS NUMBER, VAPOR PRESSURE (mm Hg @ TEMP), WEIGHT PERCENT. Rows include POLYMERIZED TUNG OIL and ALIPHATIC PETROLEUM DISTILLATES.

*** No toxic chemical (s) subject to the reporting requirements of section 313 of Title III of 40 CFR 372 are present. ***
No information available

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1) : 1.77
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C.: 73.2 g/L
SOLUBILITY IN WATER: NEGLIGIBLE
APPEARANCE AND ODOR: YELLOW TO BROWN LIQUID PASTE.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 110 DEG. F METHOD USED: TOC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1 UPPER: 6

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING WHEN FIGHTING FIRES.

UNUSUAL FIRE AND EXPLOSION HAZARDS

NONE KNOWN

SECTION V - REACTIVITY DATA

STABILITY: STABLE
CONDITIONS TO AVOID

HEAT, SPARKS AND OPEN FLAMES.

INCOMPATIBILITY (MATERIALS TO AVOID)

STRON ACIDS

HAZARDOUS DECOMPOSITION OR BYPRODUCT

NONE KNOWN

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== **SECTION VI - HEALTH HAZARD DATA** =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INHALATION OF EXCESSIVE VAPOR MAY CAUSE DIZZINESS, VOMITING, NAUSEA.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN AND EYE IRRITANT.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

MAY CAUSE DRYNESS, CRACKING.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INGESTION MAY CAUSE NAUSEA AND VOMITING.

HEALTH HAZARDS (ACUTE AND CHRONIC)

DIZZINESS, HEADACHE, NAUSEA.

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

THIS PRODUCT IS NOT LISTED IN THE NTP, IARC OR OSHA LISTS FOR CARCINOGENICITY.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

SOME SKIN CONDITIONS MAY BE AGGRAVATED.

EMERGENCY AND FIRST AID PROCEDURES

SKIN: FLUSH WITH PLENTY OF WATER. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. EYES: FLUSH WITH CLEAN WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE VICTIM TO FRESH AIR. RESTORE BREATHING IF NECESSARY. SEEK MEDICAL ATTENTION IF BREATHING REMAINS DIFFICULT. INGESTION; DO NOT INDUCE VOMITING, SEEK IMMEDIATE MEDICAL ATTENTION.

===== **SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE** =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

EXTINGUISH ALL SOURCES OF IGNITION. CONTAIN AND ABSORB WITH INERT MATERIAL.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

DO NOT STORE NEAR HEAT OR OPEN FLAMES. KEEP CONTAINER CLOSED WHEN NOT IN USE.

OTHER PRECAUTIONS

NONE KNOWN.

===== **SECTION VIII - CONTROL MEASURES** =====

REPIRATORY PROTECTION

NIOSH-APPROVED RESPIRATORS IF TLV IS EXCEEDED.

VENTILATION

LOCAL EXHAUST IS PREFERRED BUT, MECHANICAL EXHAUST IS ACCEPTABLE.

PROTECTIVE GLOVES

SOLVENT RESISTANT SUCH AS NEOPRENE.

EYE PROTECTION

SAFETY GLASSES/GOGGLES.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

SAFETY SHOWER/EYEWASH.

WORK/HYGIENIC PRACTICES

DO NOT EAT, DRINK OR SMOKE AROUND PRODUCT. WASH HANDS AFTER USE.

===== **SECTION IX - DISCLAIMER** =====

THIS INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF ACCURATE AS OF THE DATE COMPILED. HOWEVER, NO REPRESENTATION OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS.