

100 Mansell Court East, Suite 300; Roswell, GA

30076

Telephone (770) 594-0660 Fax: (770)

645-3384

Customer Service: (800) 251-6327

MATERIAL SAFETY DATA SHEET

Section 1 - Material Identity

Product Trade Name(s):

6-Tile

Common Names(s):

Kaolin Clay, China Clay

Chemical Name:

Kaolin

CAS Number:

1332-58-7 (In TSCA Inventory)

Physical Form:

White Powder

HMIS Rating

Health Hazard	1
Flammability Hazard	0
Reactivity Hazard	0
Max. Personal Protection	Е

Manufacturer's Name & Address:

IMERYS Pigments & Additives Group, 100 Mansell Court East, Suite 300;

Roswell, GA 30076

Emergency Telephone:

(800) 424-9300 CHEMTREC

Section 2 - Ingredients and Hazards

<u>Ingredient</u> Kaolin - Al ₂ Si ₂ O ₃ (OH) ₄	Wt. % (Approx.) > 98%	<u>CAS No.</u> 1332-58-7	OSHA PEL* 5 mg/m³ Resp.	ACGIH TLV* 2 mg/m³ Resp.
Crystalline Silica, Quartz	> 0.1% - ~1%	14808-60-7	15 mg/m³ Total 0.1 mg/m³ Resp.	 0.05 mg/m ³ Resp.
Water	< 2%		•	• •

^{*} Unless otherwise noted, all PEL and TLV values are reported as 8 hour time weighted averages (TWA).

Section 3 - Hazards Identification and Cautions

Appearance: White Powder

Primary Routes of Entry: Skin contact, skin absorption, eye contact, ingestion: Hazard Classification - None.

(Historical basis for

classification.)

Target Organs: Eye, skin and lungs

Medical Conditions Aggravated by Exposure: Skin contact may aggravate existing dermatitis. Breathing excessive quantities of kaolin dust may aggravate pre-existing respiratory conditions.

Potential Health Effects:

Eye Contact: This product may produce irritation upon contact with the eye. See also Section 4 below.

Skin Contact: Prolonged or repeated exposure may cause skin irritation. Kaolin is not expected to be absorbed through the skin in harmful amounts or to produce an allergic skin reaction. See also Section 4 below.

Ingestion: No adverse effect is expected. If ingested, seek medical advice. See also Section 4 below.

Inhalation: Inhalation of excessive quantities of kaolin dust may irritate the respiratory tract. Prolonged exposure to respirable kaolin dust without use of appropriate respiratory equipment could adversely affect respiratory function including fibrogenic response. See Am. Rev. Respir. Dis. 1983; 127:215-220; 231-253; 141-142; Doc. Thres. Limit Values and Bio. Exp. Ind., Sixth Edition, 1991: OSHA PEL-29 C.F.R. 1910.1000.

Subchronic, Chronic: None expected. No applicable information was found concerning any potential health effects resulting from subchronic or chronic exposure to kaolin.

This product typically contains crystalline silica (quartz sand) above 0.1% as a naturally occurring impurity. The International Agency for Research on Cancer has concluded that "crystalline silica inhaled in the form of quartz or

cristobalite from occupational sources is carcinogenic to humans (Group I)." It also noted that carcinogenicity was not detected in all industrial circumstance studies, and may be dependent on external factors affecting its biological activity or distribution of its polymorphs. (See IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Volume 68 (1997).) Exposure to respirable silica has also been associated with silicosis, scleroderma, and nephrotoxicity. (See Occupational Lung Disorders, Third Edition, Chapter 12 (1994) and American Journal of Respiratory and Critical Care Medicine, Volume 155, pp 761-765 (1997).)

Section 4 - First Aid Measures

Eye Contact: Follow good industrial hygiene practices. In case of contact, immediately flush eyes with plenty of water. Seek medical

aid if necessary.

Skin Contact: Follow good industrial hygiene practices. Wash affected skin areas thoroughly with soap and water.

Seek medical aid if necessary.

Inhalation: Follow good industrial hygiene practices. If excessive exposure by inhalation is suspected, remove to

fresh air. If necessary, a MSHA/NIOSH or OSHA/NIOSH approved respirator is recommended.

Seek medical aid if necessary.

Ingestion: Follow good industrial hygiene practices. If ingested, do not induce vomiting. If conscious, drink

two glasses of water. Seek medical aid if necessary.

Section 5 - Fire Fighting Measures

Explosion Data: Not Explosive Flammability: Not Flammable or Combustible

LEL: Not Applicable Flash Point: Not Applicable
UEL: Not Applicable Auto-Ignition: Not Applicable

Extinguishing Media: Product will not burn.

NFPA 704M Hazard Classification: Health: 1 Flammable: 0 Reactivity: 0

Use appropriate extinguishing media for packaging material if applicable.

Section 6 - Accidental Release Measures

Vacuum, pump or scoop spilled material into containers for reclaiming or disposal. Use proper respiratory and personal protective equipment. MSHA/NIOSH or OSHA/NIOSH approved respirator recommended. Spilled materials may cause slippery conditions when wet. Care should be exercised when walking on spills on floors or concrete pads. No neutralizing chemicals required. Material is inert and nonreactive. Kaolin is not a CERCLA listed hazardous substance.

Section 7 - Handling and Storage

Storage in a cool, dry location is recommended.

Spilled materials may cause slippery conditions when wet. Care should be exercised when walking on spills on floors or concrete

pads.

Minimize dust generation & accumulation.

If excessive dust is generated, provide adequate ventilation and use proper respiratory and personal protective equipment.

MSHA/NIOSH or OSHA/NIOSH approved respirator recommended

Section 8 - Exposure Control/Personal Protection

<u>Hazardous</u> Ingredient	Weight %(Approx.)	CAS No.	MSHA PEL	OSHA PEL	ACGIH TLV
THE TOTAL CONTRACT OF THE PARTY	75(12)	1332-58-7	10mg/cu.m. Total	15mg/cu.m. Total 5 mg/cu.m. Resp.	2 mg/cu.m. Respirable
Crystalline Silica, Quartz	> 0.1% - ~1%	14808-60-7	0.1 mg/m3 Resp	0.1 mg/m ³ Resp.	0.05 mg/m ³ Resp.

Unless otherwise noted, all PEL and TLV values are reported as 8 hour time weighted averages (TWA).

Respiratory Protection: If respirator is required, use of a MSHA/NIOSH or OSHA/NIOSH approved respirator is

recommended.

Ventilation: Use exhaust ventilation, if required, to maintain dust concentration below recommended

exposure limits.

Protective Equipment: Wear side shield safety glasses. Rubber gloves are recommended for prolonged exposure.

Section 9 - Physical and Chemical Properties

Boiling Point: Not Applicable Solid **Physical State:** Not Applicable Odorless, white powder Freezing Point: Appearance & Odor: Vapor Pressure: Not Applicable 4.0 - 6.0pH (Aqueous Suspension): Not Applicable Specific Gravity: Vapor Density: ~2.6 None VOC: % Solubility in Water: Insoluble

Melting Point:	Not Determined, > 1500°C	Evaporation Rate:	Not Applicable		
	Section 10 - Stability and	d Reactivity			
Chemically Stable? Yes X Compatible with Other Subst Hazardous Decomposition/By Conditions Contributing to H		nonreactive. on or by-products expected. Inert an t and nonreactive.	d nonreactive.		
	Section 11 - Disposal Co	nsiderations			
EPA Waste Number: Under F state and federal requirements.	CRA (40 CFR 261) kaolin is a non-haz	zardous waste. Dispose of waste ma	terial in accordance with all local,		
	Section 12 - Toxi	cological Information			
kaolin - CAS No. 1332-58-7 Primary Route of Exposure:	X Skin; X Eye Contact; X In	halation; Ingestion			
Skin contact may aggravate ex Inhalation from prolonged and respiratory conditions. No adverse effect expected wh	continuous exposure to excessive quan		asthmatic or		
Chronic Health Hazards: Prolonged inhalation of excessive levels of kaolin dust may cause a simple pneumoconiotic condition, not normally associated with a decrement in lung function. In cases of long term exposure to extremely high levels of dust, complicated pneumoconiosis with lung function impairment may occur.					
Carcinogenicity*: NTP? No	IARC? No	OSHA? <u>No</u>			
Mutagenicity: None known	Teratogenicity: None know	n Reproductive Effects:	None known		
* See Section 3 for discussion of crystalline silica.					
	Section 13 - Transport	Information			
EPA Waste Number: DOT Classification: Not Reg Internal UN:	Not Regulated ulated DOT/IMO Classificatio Not Regulated	n: Not Regulated			
	Section 14 - Regulatory	Information			
FDA: Kaolin is as generally re established as a component of	cognized as safe (GRAS) under the FD. the uncoated or coated food-contact sur	A in accordance with 21 CFR 186.13	256. Additionally, kaolin is ordance with 21 CFR 176.170		

(aqueous and fatty foods) and 21 CFR 176.180 (dry foods).

SARA Title III Section 302 Extremely Hazardous Substances: This product does not contain extremely hazardous substances subject to the reporting requirements of Section 302 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 355.

SARA Title III Section 311 and 312 Health and Physical Hazard Categories per 40 CFR 370.2:

<u>Fire</u> **Pressure** Reactivity **Immediate Delayed** No Yes Yes No

SARA Section 313 Notification: This product does not contain toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

TSCA: Product is listed in Initial Inventory, Vol. 1, Appendix A, CAS No. 1332-58-7.

The International Agency for Research on Cancer has concluded that "crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group I)." It also noted that carcinogenicity was not detected in all industrial circumstance studies, and may be dependent on external factors affecting its biological activity or distribution of its polymorphs. (See IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Volume 68 (1997).) Exposure to respirable silica has also been associated with silicosis, scleroderma, and nephrotoxicity. (See Occupational Lung Disorders, Third Edition, Chapter 12 (1994) and American Journal of Respiratory and Critical Care Medicine, Volume 155, pp 761-765 (1997).)

WARNING: This product may also contain extremely small amounts of one or more naturally-occurring materials known to the State of California to cause cancer, birth defects, or other reproductive harm.

While this information and recommendations set forth herein are believed to be accurate as of the date hereof, IMERYS PIGMENTS & ADDITIVES GROUP MAKES NO WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT HERETO

Page 4 of 4

AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

IMERYS is a business name of IMERYS Pigments, Inc., IMERYS Kaolin, Inc. and IMERYS Marble, Inc. Registered in the USA. Registered Office: 100 Mansell Court East, Suite 300, Roswell, GA 30076.

Date Prepared: <u>07/27/82</u> **Revised:** <u>06/2000</u>